

Allied Chemicals SC

Technical Data Sheet of Calcite

Product Name: Calcite

Product Code: ACSCC

CAS No: 13397-26-7

Description: Calcite is a colourless or white mineral (occasionally tinged with impurities), found in sedimentary and metamorphic rocks, in veins, in limestone, and in stalagmites and stalactites. It is used in the manufacture of cement, plaster, paint, glass, and fertilizer. It is the most stable polymorph of calcium carbonate

1. Physical Properties:

Colour & Appearance: White free flowing powder without any visible contamination

CaCO₃ : 86 to 92%

PH (5% Aq. Soln.) : 7-10

Moisture : 0.4% Max

2. Chemical Composition:

Active Ingredients: Calcium carbonate

Hazardous Ingredients: None

3. Applications:

Calcite is used for wide range of applications such as:

- o In Calcite is used as an antacid or as a calcium supplement
- It is also used as filler in cosmetics
- o It is added to swimming pools as a disinfectant agent and a pH corrector
- It finds extensive usage in the manufacturing industry as a building material (marble), ingredient for quick lime and cement.
- Calcite is the most widely used mineral in the paper, plastics, paints and coatings industries both as a filler - and due to its special white colour - as a coating pigment.
- Calcite is considered as an additive in the production of pesticides and poultry food. Natural calcium carbonate products are suitable and friendly with the environment
- Calcite forms a kind of internal frame structure in plastic products, and greatly improves the dimensional stability of plastic products. It can improve the product hardness, electrical efficiency, flame retardant performance, heat resistance and treatment performance.



Allied Chemicals SC

- Calcite is widely used when combined with polyethylene resins to manufacture bags, packaging, shopping bags, bags, clothes bags, garbage bags.
- Using calcium carbonate increases product durability, better dispersion in plastic chemicals, optimal product gloss, and improved production process.
- Calcite is widely used when combined with polypropylene with high MI to produce injection moulding of plastic products such as Sheets, hollow boards, household items, and home appliances accessories.

4. Storage and Handling:

- o Keep containers or bag tightly closed in a dry and well-ventilated place.
- Wear personal protective equipment. Ensure adequate ventilation. Avoid contact with skin, eyes or clothing. Avoid ingestion and inhalation. Avoid dust formation

5. Packaging:

Calcite is available in 25kg, 50kg, Jumbo bags and various bag sizes.

6. Shelf Life:

The product typically has a shelf life of 24 months from the date of manufacture when stored as recommended.

7. Safety and Environmental Precautions:

Calcite is intended for industrial use only.

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Disclaimer: This technical data sheet is for informational purposes only and does not constitute a warranty or guarantee regarding the product's performance. Users should conduct their own tests to determine the suitability of Calcium Carbonate for their specific applications.